

GOOSENECK/PINTLE

TRAILERS

VAN BODY TO BE TRAILER
UPPER AND LOWER DECKS MUST
NO STAKE POCKETS OR RAILS 90" WIDE OR
USE 8T-09H HARNESSES W/JUNCTION BOX
WHEEL COVERS MUST BE CLIP TO FIT
HARNESSES & AIR TO RUN TH BOTTOM OF FRAME
DO NOT CAP FLOOR (SCREWS ONLY)
NO BIG TEX DECKS
LIGHTING PER DODG
WIRE UPPER DECK HARNESSES INTO 7-WAY SOCKET
LEVEL ALL CONNECTIONS IN STRONG AND SUPPLY
WIRE UPPER DECK OUT OF LEVEL WHEN FINISHED

#1 Selling Trailer

BigTex TRAILERS

Largest Selection
Highest Quality
Best Value



Tough As A Texas Longhorn



TANDEM AXLE GOOSENECK

14GN

STANDARD FEATURES

Standard Sizes Available: 8½' x 20' ■ 8½' x 22' ■ 8½' x 24' ■ 8½' x 26' ■ 8½' x 28'



- ▶ G.V.W.R. 14,000#
- ▶ G.A.W.R. (Ea. Axle) 6,084#
- ▶ Coupler 2-5/16" Ball Adjustable Pipe
- ▶ Safety Chains 3/8" Grd. 70 w/Safety Latch Hook (2 ea.)
- ▶ Jack 10,000# Drop Leg Jack (Bolted On)

- ▶ Neck 10" Channel
- ▶ Top Rail (none)
- ▶ Frame 12" - 16# I-Beam
- ▶ Crossmembers 3" Channel
- ▶ Side Rails 5" channel w/ Rub Rail and Stake Pockets on 24" Centers

- ▶ Axles Two 7000# Cambered Axles w/ Elec. Brakes
- ▶ Suspension Multi-Leaf Slipper Spring w/ Equalizer
- ▶ Tire LT235/85R16 Load Range E
- ▶ Wheel 6.00 X 16" HD White Modular - 8 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 6 Way
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

TRIPLE AXLE GOOSENECK

18GN

STANDARD FEATURES

Standard Sizes Available: 8½' x 24' ■ 8½' x 26' ■ 8½' x 28' ■ 8½' x 30' ■ 8½' x 32' ■ 8½' x 34'



- ▶ Axles Three 6000# Cambered Axles w/ Elec. Brakes
- ▶ Suspension Multi-Leaf Slipper Spring w/ Equalizers
- ▶ Tire LT235/85R16 Load Range E
- ▶ Wheel 6.00 X 16" White Spoke 8 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 6 Way
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

- ▶ G.V.W.R. 18,000#
- ▶ G.A.W.R. (Ea. Axle) 6,000#
- ▶ Coupler 2-5/16" Ball Adjustable Pipe
- ▶ Safety Chains 3/8" Grd. 70 w/Safety Latch Hook (2 ea.)
- ▶ Jack 10,000# Drop Leg Jack (Bolted On)

- ▶ Neck 10" Channel
- ▶ Top Rail (none)
- ▶ Frame 12" - 16# I-Beam
- ▶ Crossmembers 3" Channel
- ▶ Side Rails 3" X 5" X ¼" Angle w/ Rub Rail and Stake Pockets on 24" Centers/Back

TANDEM DUAL GOOSENECK / PINTLE

20GN / 20PH

STANDARD FEATURES

Standard Sizes Available: 8½' x 20' ■ 8½' x 24'



- ▶ G.V.W.R. 20,000#
- ▶ G.A.W.R. (Ea. Axle) 9,000#
- ▶ Coupler 2-5/16" Ball Adjustable Pipe or Pintle
- ▶ Safety Chains 3/8" Grd. 70 w/ Safety Latch Hook (2 ea.)
- ▶ Jack 10,000# Drop Leg Jack (Bolted On)

- ▶ Neck 10" Channel (If Applicable)
- ▶ Top Rail (none)
- ▶ Frame 12" - 16# I-Beam
- ▶ Crossmembers 3" Channel
- ▶ Side Rails 3" X 5" X ¼" Angle w/ Rub Rail and Stake Pockets on 24" Centers

- ▶ Axles Two 9000# Dual Wheel Electric Brake Axles
- ▶ Suspension Multi-Leaf Slipper Spring w/ Equalizer
- ▶ Tire 750 X 16 Load Range E
- ▶ Wheel 16 X 6 Dual 8 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 6 Way
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

12GP**HEAVY DUTY GOOSENECK TANDEM AXLE TRAILER****STANDARD FEATURES**

Standard Sizes Available: 7' x 18' ■ 7' x 20' ■ 7' x 22' ■ 7' x 24'



- ▶ G.V.W.R. 12,000#
- ▶ G.A.W.R. (Ea. Axle) 5,560#
- ▶ Coupler 2-5/16" Ball Adjustable Pipe
- ▶ Safety Chains 3/8" Grd. 70 w/ Safety Latch Hook (2 ea.)
- ▶ Jack 10,000# Dropleg Jack (Bolted On)
- ▶ Neck 8" Channel
- ▶ Top Rail 2-7/8" Pipe Square Back
- ▶ Frame 3" X 5" X 1/4" Angle
- ▶ Crossmembers 2" X 3" X 3/16" Angle
- ▶ Uprights 2" X 3" X 3/16" X 16"
- ▶ Fenders 9" X 72" Double Broke Diamond Plate w/ Back

- ▶ Axles Two 6000# Cambered Axles w/ Elec. Brakes
- ▶ Suspension Multi-Leaf Slipper Spring with Equalizer
- ▶ Tire 7.50 X 16" Load Range E
- ▶ Wheel 16 X 6 White Spoke 8 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 6 Way
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

HEAVY DUTY GOOSENECK TANDEM AXLE TRAILER**14GP****STANDARD FEATURES**

Standard Sizes Available: 7' x 18' ■ 7' x 20' ■ 7' x 22' ■ 7' x 24' ■ 7' x 26'



- ▶ Axles Two 7000# Cambered Axles w/ Elec. Brakes
- ▶ Suspension Multi-Leaf Slipper Spring w/ Equalizer
- ▶ Tire LT235/85R16 Load Range E
- ▶ Wheel 16 X 6 HD White Modular 8 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 6 Way
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

- ▶ G.V.W.R. 14,000#
- ▶ G.A.W.R. (Ea. Axle) 6,084#
- ▶ Coupler 2-5/16" Ball Adjustable Pipe
- ▶ Safety Chains 3/8" Grd. 70 w/ Safety Latch Hook (2 ea.)
- ▶ Jack 10,000# Drop Leg Jack (Bolted On)
- ▶ Neck 8" Channel
- ▶ Top Rail 3" Square Tubing
- ▶ Frame 3" X 5" X 5/16" Angle
- ▶ Crossmembers 3" Channel
- ▶ Uprights 16" Tall 2" X 3" X 3/16" Angle
- ▶ Fenders 9" X 72" Dbl. Broke Diamond Plate w/Back

12GN**TANDEM AXLE GOOSENECK****STANDARD FEATURES**

Standard Sizes Available: 8' x 20' ■ 8' x 22' ■ 8' x 24' ■ 8' x 26'



- ▶ G.V.W.R. 12,000#
- ▶ G.A.W.R. (Ea. Axle) 6,000#
- ▶ Coupler 2-5/16" Ball Adjustable Pipe
- ▶ Safety Chains 3/8" Grd. 70 w/ Safety Latch Hook (2 ea.)
- ▶ Jack 10,000# Drop Leg Jack (Bolted On)
- ▶ Neck 10" Channel
- ▶ Top Rail (none)
- ▶ Frame 12" - 16" I-Beam
- ▶ Crossmembers 3" channel
- ▶ Side Rails 3" X 5" X 1/4" Angle w/ Rub Rail and Stake Pockets on 24" Centers

- ▶ Axles Two 6000# Cambered Axles w/ Elec. Brakes
- ▶ Suspension Multi-Leaf Slipper Spring w/ Equalizer
- ▶ Tire 7.50-16LT Load Range E
- ▶ Wheel 6.00 X 16" White Spoke 8 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 6 Way
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

TANDEM DUAL AXLE GOOSENECK/PINTE

22GN/22PH

STANDARD FEATURES

Standard Sizes Available: 8½' x 20' thru 40'

Shown with optional dovetail



- G.V.W.R. 22,500#
- G.A.W.R. (Ea. Axle) 10,000#
- Coupler 2-5/16" Ball Adj. Square Crank Type
- Safety Chains 3/8" Grd. 70 w/Safety Latch Hook (2 ea.)
- Jacks Two 10,000# Drop Leg Jacks (Bolted On)

- Neck 10" Channel
- Top Rail (none)
- Frame 12" - 16# I-Beam w/Bridge Truss
- Crossmembers 3" Channel
- Side Rails 6" Channel w/Rub Rail and Stake Pockets on 24" Centers

- Axles Two 10,000# Dual Wheel Electric Brake Axles (Oil Bath)
- Suspension Multi-Leaf Slipper Spring with Equalizer
- Tire LT235/85R16 Load Range E
- Wheel 16 X 6 Dual 8 Bolt
- Floor 2" Pine
- Lights D.O.T. Stop, Tail, Turn and Clearance
- Elec. Plug 6 Way
- Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

TANDEM DUAL AXLE GOOSENECK

25GN

STANDARD FEATURES

Standard Sizes Available: 8½' x 20' thru 40'

Shown with optional dovetail



- Axles Two HD 10,000# Dual Wheel Electric Brake Axles (Oil Bath)
- Suspension Hutch 9700 Adjustable
- Tire LT235/85R16 Load Range E
- Wheel 16 X 6 Dual 8 Bolt
- Floor 2" Pine
- Lights D.O.T. Stop, Tail, Turn and Clearance
- Elec. Plug 6 Way
- Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

- G.V.W.R. 25,900#
- G.A.W.R. (Ea. Axle) 10,000#
- Coupler 2-5/16" Ball Square Crank Type
- Safety Chains 3/8" Grd. 70 w/Safety Latch Hook (2 ea.)
- Jacks Two Speed Landing Gear Jack Set 150,000# Capacity (Bolted On)

- Neck 12" Channel
- Frame 12" - 16# I-Beam
- Crossmembers 3" Channel
- Side Rails 8" Channel w/Rub Rail and Stake Pockets on 24" Centers