

# SINGLE AXLE

# TRAILERS

VAN BODY TO BE TRAILER  
UPPER AND LOWER DECKS MUST  
NO STAKE POCKETS OR SUBRAILS 90" WIDE OR  
USE ST-099 HARNESS W/JUNCTION BOX  
WHEEL COVERS MUST BE CLIP TO FIT  
HARNESS & AIR TO RUN TH BOTTOM OF FRAME  
DO NOT CAP FLOOR (SCREWS ONLY)  
NO BIG TEX DECKS  
LIGHTING PER DODG  
WIRE UPPER DECK HARKERS INTO 7-WAY SOCKET  
LEVEL ALL SURFACES TO STANDARDS AND SUPPL  
WIRE UPPER DECK HARKERS INTO 7-WAY SOCKET

*#1 Selling Trailer*

# BigTex TRAILERS

**Largest Selection**  
**Highest Quality**  
**Best Value**



**Tough As A Texas Longhorn**



## SINGLE AXLE UTILITY TRAILER

**29SA**



### STANDARD FEATURES

Standard Sizes Available: 5' x 10' ■ 5' x 14'

- ▶ G.V.W.R. 2,995#
- ▶ G.A.W.R. (Ea. Axle) 2,960#
- ▶ Coupler 2" Coupler
- ▶ Safety Chains 1/4" Grd. 30 w/Safety Latch Hook (2 ea.)
- ▶ Jack 2000# Top Wind (Bolted On)
- ▶ Tongue 3" x 2" x 3/16 Angle
- ▶ Top Rail 2" x 2" 1/8" Angle
- ▶ Frame 2" x 3" x 3/16 Angle
- ▶ Crossmembers 2" x 3" x 3/16 Angle
- ▶ Uprights 14" Tall 2" x 2" x 1/8 Angle
- ▶ Fenders 9" X 32" Rolled Formed w/Back

- ▶ Axle 3500# Cambered Axle
- ▶ Suspension Multi-Leaf Spring
- ▶ Tire ST205/75-15 Load Range B
- ▶ Wheel 15 X 5 White 5 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 4 Way Flat w/Loom
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel.

## SINGLE AXLE UTILITY TRAILER

**30SA**

### STANDARD FEATURES

Standard Sizes Available: 5' x 8' ■ 5' x 10' ■ 5' x 12' ■ 5' x 14'

- ▶ Axle 3500# Cambered Axle w/ Brake Flanges
- ▶ Suspension Multi-Leaf Spring
- ▶ Tire ST205/75-15 Load Range B
- ▶ Wheel 15 x 5 White Spoke 5 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 4 Way Flat w/ Loom
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped



Shown with tilt option

- ▶ G.V.W.R. 2,995#
- ▶ G.A.W.R. 2,960#
- ▶ Coupler 2" A-Frame
- ▶ Safety Chains 1/4" Grd. 30 w/Safety Latch Hook (2 ea.)
- ▶ Jack 2000# Top Wind (Bolted On)
- ▶ Tongue 3" Channel Tongue
- ▶ Top Rail 2-3/8" Pipe Square Back
- ▶ Frame 2" X 3" X 3/16" Angle
- ▶ Crossmembers 2" X 3" X 3/16" Angle
- ▶ Uprights 15" Tall 2" X 2" X 1/8" Angle
- ▶ Fenders 9" X 32" Rolled Formed w/ Back

## SINGLE AXLE UTILITY TRAILER

**35SA**



Shown with gate option

### STANDARD FEATURES

Standard Sizes Available: 6 1/2' x 10' ■ 6 1/2' x 12' ■ 6 1/2' x 14'

- ▶ G.V.W.R. 2,995#
- ▶ G.A.W.R. 2,960#
- ▶ Coupler 2" A-Frame
- ▶ Safety Chains 1/4" Grd. 30 w/Safety Latch Hook (2 ea.)
- ▶ Jack 2000# Top Wind (Bolted On)
- ▶ Tongue 3" Channel Tongue
- ▶ Top Rail 2-3/8" Pipe Square Back
- ▶ Frame 2" X 3" X 3/16" Angle
- ▶ Crossmembers 2" X 3" X 3/16" Angle
- ▶ Uprights 15" Tall 2" X 2" X 1/8" Angle
- ▶ Fenders 9" X 32" Rolled Formed w/ Back

- ▶ Axle 3500# Cambered Axle w/ Brake Flanges
- ▶ Suspension Multi-Leaf Spring
- ▶ Tire ST205/75-15 Load Range B
- ▶ Wheel 15 x 5 White Spoke 5 Bolt
- ▶ Floor 2" Pine
- ▶ Lights D.O.T. Stop, Tail, Turn and Clearance
- ▶ Elec. Plug 4 Way Flat w/ Loom
- ▶ Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- ▶ Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

**15LT****LIL TEX UTILITY TRAILER**

Shown with gate option

**STANDARD FEATURES**

Standard Sizes Available: 4' x 8'

- G.V.W.R. 1,500#
- G.A.W.R. 1,560#
- Coupler 2" Coupler
- Safety Chains 1/4" Grd. 30 w/Safety Latch Hook (2 ea.)
- Jack (none)

- Tongue Single 2" X 3" Tubing
- Top Rail 2" X 2" X 1/8" Angle
- Frame 2" X 2" X 1/8" Angle
- Crossmembers 2" X 2" X 1/8" Angle
- Uprights 10" Tall 2" X 2" X 1/8" Angle
- Fenders 7" X 28" Rolled Formed

- Axle 2000# Cambered Axle
- Suspension Multi-Leaf Slipper Spring
- Tire 4.80-12" Load Range B
- Wheel 12 x 4 White Spoke 5 Bolt
- Floor 2" Pine
- Lights D.O.T. Stop, Tail, Turn and Clearance
- Elec. Plug 4 Way Flat w/ Loom
- Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

**SINGLE AXLE ALL-AROUND UTILITY TRAILER****15AA-8****STANDARD FEATURES**

Standard Sizes Available: 4' x 8'

- Axle 2000# Cambered Axle
- Suspension Multi-Leaf Slipper Spring
- Tire 20.5 x 8.0-10 Load Range B
- Wheel 5 Bolt 10 x 6
- Floor Expanded Metal
- Lights D.O.T. Stop, Tail, Turn and Clearance
- Elec. Plug 4 Way Flat w/ Loom
- Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped



Shown with gate option

- G.V.W.R. 1500#
- G.A.W.R. 1810#
- Coupler 2" Coupler
- Safety Chains 1/4" Grd. 30 w/Safety Latch Hook (2 ea.)
- Jack (none)

- Tongue Single 2 x 3 Tubing
- Frame 2 x 2 x 1/8 Angle
- Crossmember 2 x 2 x 1/8 Angle
- Fenders 9" x 25" Jeep Style
- Sides 14 Ga Fabricated Smooth

**19SL****SUPER LIL TEX UTILITY TRAILER**

Shown with optional fold-up jack

**STANDARD FEATURES**

Standard Sizes Available: 4 1/2' x 9'

- G.V.W.R. 1,995#
- G.A.W.R. 2,000#
- Coupler 2" A-Frame
- Safety Chains 1/4" Grd. 30 w/Safety Latch Hook (2 ea.)
- Jack 2000# Top Wind (Bolted On)

- Tongue 3" Channel - V-Tongue
- Top Rail 2" X 2" X 1/8" Angle
- Frame 3" X 2" X 3/16" Angle
- Crossmembers 2" X 2" X 1/8" Angle
- Uprights 11" Tall 2" X 2" X 1/8" Angle
- Fenders 9" X 32" Square

- Axle 2000# Cambered Axle
- Suspension Multi-Leaf Spring
- Tire ST175/80 - 13" Load Range B
- Wheel 13 x 4.5 White Spoke 5 Bolt
- Floor 2" Pine
- Lights D.O.T. Stop, Tail, Turn and Clearance
- Elec. Plug 4 Way Flat w/ Loom
- Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

**30AA / 35AA****SINGLE AXLE ALL-AROUND TRAILER****STANDARD FEATURES**

Standard Sizes Available: 5' x 10' ■ 6½' x 10'

- G.V.W.R. 2,995#
- G.A.W.R. 2,960#
- Coupler 2" A-Frame
- Safety Chains ¼" Grd. 30 w/Safety Latch Hook (2 ea.)
- Jack 2000# Top Wind (Bolted On)

- Tongue 3" Channel
- Sides (16 Ga.) 14" Solid Formed
- Side Panels w/ 2" Lip
- Frame 2" X 3" X 3/16" Angle
- Crossmembers 2" X 3" X 3/16" Angle
- Fenders 9" X 32" Rolled FV

- Axle 3500# Cambered Axle w/ Brake Flanges
- Suspension Multi-Leaf Spring
- Tire ST205/75-15 Load Range B
- Wheel 15 x 5 White Spoke 5 Bolt
- Floor 2" Pine
- Lights D.O.T. Stop, Tail, Turn and Clearance
- Elec. Plug 4 Way Flat w/ Loom
- Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped

**SINGLE AXLE PAN TILT TRANSPORT****60TP****STANDARD FEATURES**

Standard Sizes Available: 6½' x 12'

- Axle One 6000# Torflex Electric Brake Axle
- Suspension Torsion
- Tire LT235/85R16 Load Range E
- Wheel 16 X 6 White Spoke 8 Bolt
- Lights D.O.T. Stop, Tail, Turn and Clearance
- Elec. Plug 6 Way Round
- Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped



- G.V.W.R. 6,000#
- G.A.W.R. 6,000#
- Coupler Adjustable 2-5/16"
- Safety Chains ¼" Grd. 70 w/ Safety Latch (2 ea.)
- Jack 2000# Swivel Mount

- Tongue 2" X 4" Square Tubing
- Bed 3/16" Steel Pan
- Crossmembers 3" Channel
- Fenders 16 Ga. Jeep Style

**35MC-13****SINGLE AXLE MOTOR CYCLE TRAILER**

Shown with gate option

**STANDARD FEATURES**

Standard Sizes Available: 6½' x 13'

- G.V.W.R. 2,995#
- G.A.W.R. 2,960#
- Coupler 2" Bulldog Coupler
- Safety Chains ¼" Grd. 30 w/ Safety Latch Hook (2 ea.)
- Jack 2000# Top Wind Fold Up Jack

- Tongue Integral w/ Frame
- Frame 2" X 4" Tubing
- Crossmembers 2" X 3" X 3/16" Angle
- Fenders 9" X 32" Rolled Formed w/ Back

- Axle 3500# Cambered Axle w/ Brake Flange
- Suspension Torsion
- Tire ST205/75-15 Load Range B
- Wheel 15 X 6 5-Bolt Chrome
- Floor 1/8" Diamond Plate
- Lights D.O.T. Stop, Tail, Turn and Clearance
- Elec. Plug 4-Way Flat w/ Loom
- Finish (prep) Acid Etched w/White Phosphorus, & Two Coats Primer
- Finish Painted w/ 2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped